



PRODUCT SPECIFICATIONS

Surface: sheet steel, powder-coated
 Rear panel: aluminum, untreated
 Field of application: direct heating
 Surface temperature: approx. 90° C to 110° C
 Voltage: 230 Volt, 50/60 Hz
 Colour: white
 Safety specs: IP 45, protection class 1
 Temperature protection: 1-2 sensors, depending on heater dimensions
 Power supply: Type CEE 7/7 tilted; cable length: 1.9 m

Certificates:



MODEL	DIMENSIONS [mm]	NOMINAL OUTPUT [W]	WEIGHT [kg]	HEATABLE AREA [m ²]
Heat4All SmartLine 175	495 x 350 x 16	170	2.35	2-5
Heat4All SmartLine 320	595 x 595 x 16	320	4,3	4-8
Heat4All SmartLine 520	950 x 615 x 16	520	6.75	8-12
Heat4All SmartLine 700	1100 x 650 x 16	700	8,2	11-19
Heat4All SmartLine 1000	1240 x 815 x 16	1000	11.2	16-24

LIGHT FRAME	DIMENSIONS [mm]	NOMINAL OUTPUT [W]	LUMEN
Light Frame SmartLine 175	536 x 391 x 20	26	2,200
Light Frame SmartLine 320	636 x 636 x 20	37	3,100
Light Frame SmartLine 520	991 x 656 x 20	47	4,000
Light Frame SmartLine 700	1141 x 691 x 20	53	4,600
Light Frame SmartLine 1000	1281 x 856 x 20	62	5,400

CONTROL SYSTEMS

To remotely control your Heat4All SmartLine panels we offer Heat4All as well as HomeMatic thermostats and actuators. For additional info, please take a look at pages 34 and 35 or visit www.heat4all.com.

Details SmartLine Panels – silver/white frame

